

LITTELFUSE SHOCK-BLOCK[®] SB3000 PRODUCTS

SB3000 Series



Description

Littelfuse Shock-Block provides ground-fault protection to production equipment from electrical hazards. Wet conditions, moisture or just worn cable insulation can cause ground fault conditions. Shock-Block ground-fault protection monitors leakage current to eliminate potential electrical hazards caused by wet equipment.

The SB3000 series does not provide GFCI protection. For more information on available GFCI products that can be used with the SB3000 series, have a look at the [SB100B](#), [SB250B](#), and [LB100GFCI](#).

Ordering Information

MODEL	CURRENT CAPACITY	VOLTAGE	PHASE	SHIPPING WEIGHT	SHIPPING DIMENSION
SB3200	200A	120/208 - 240 VAC	Three	90 lbs	16" L x 23" W x 28" H
SB3400	400A	120/208 240-480 VAC	Three	220 lbs	26" L x 31" W x 55" H
SB3800	800A	120/208 240-480 VAC	Three	-	-

Product Features

- Portable, in-line plug-in device
- UL Listed
- Dimmable Options available (see model SB100B)

Specifications

- Voltage Rating:** 120VAC – 480VAC
- Amperage Ratings:** 200 – 800 amperes
- Trip Level:** 10 mA
- Phase:** Three
- Enclosure:** NEMA Type 4 / 4X
- Approval:** UL Listed
- Connection:** Cam Lock

Web Resources

www.littelfuse.com/shockblock

For more information, contact the Littelfuse Shock-Block Sales and Leasing Office at **818-764-7585**, or visit www.littelfuse.com/shockblock